

In the Claims:

1. (previously amended) An angle measuring device for measuring an angular position of a stationary object with respect to an object which is rotatable around an axis of rotation, comprising:

a rotor comprising a graduation, which is connected to said rotatable object, which rotates about an axis of rotation;

a stator comprising a scanning unit for scanning said graduation, which rotates in relation to said scanning unit;

a coupler fastened to said stator so as to seat said stator on said stationary object that comprises a contact face which extends transversely with respect to said axis of rotation, wherein said coupler comprises a contact face that extends transversely with respect to said axis of rotation and engages said contact face of said stationary object so that a clamping force is generated so as to fasten said coupler to said stationary object and wherein said coupler is fixed against relative rotation, but is radially and/or axially elastic.

2. (original) The angular measuring device in accordance with claim 1, wherein said coupler is clamped against a circumferential face of said stationary object.

3. (previously amended) An angle measuring device for measuring an angular position of a stationary object with respect to an object which is rotatable around an axis of rotation, comprising:

a rotor comprising a graduation, which is connected to said rotatable object, which rotates about an axis of rotation;

a stator comprising a scanning unit for scanning said graduation, which moves in relation to said scanning unit;

a coupler fastened to said stator by being clamped against a circumferential face of said stationary object so as to seat said stator on said stationary object that comprises a contact face which extends transversely with respect to said axis of rotation, wherein said coupler comprises a contact face that extends transversely with respect to said axis of rotation and engages said contact face of said stationary object so that a clamping force is generated so as to fasten said coupler to said stationary object and wherein said coupler is fixed against relative rotation, but is radially and/or axially elastic, wherein said coupler comprises an area which is radially spread against an inner face and circumferential face of said stationary object.

4. (original) The angular measuring device in accordance with claim 1, wherein said coupler comprises an area which is axially spread into a gap of said

stationary object.

5. (original) The angular measuring device in accordance with claim 1,
wherein said coupler comprises:

a base that is fastened on said stator; and

a plurality of tongues formed on said base that clamp said coupler to said
stationary object.

6. (original) The angular measuring device in accordance with claim 2,
wherein said coupler comprises:

a base that is fastened on said stator; and

a plurality of tongues formed on said base that clamp said coupler to said
stationary object.

7. (original) The angular measuring device in accordance with claim 3,
wherein said coupler comprises:

a base that is fastened on said stator; and

a plurality of tongues formed on said base that clamp said coupler to said
stationary object.

8. (original) The angular measuring device in accordance with claim 4, wherein said coupler comprises:

a base that is fastened on said stator; and

a plurality of tongues formed on said base that clamp said coupler to said stationary object.

9. (original) The angular measuring device in accordance with claim 5, wherein one of said plurality of tongues comprises a wave-shaped bend positioned between said base and a clamping place, where said one of said plurality of tongues clamps said coupler to said stationary object.

10. (original) The angular measuring device in accordance with claim 1, wherein said coupler comprises:

two diametrically oppositely located tongues that are fastened to said stator; and

two further diametrically oppositely located tongues, which are offset by 90° with respect to said two diametrically oppositely located tongues that are fastened to said stator, and wherein clamping takes place between said two further diametrically oppositely located tongues and said stationary object.

11. (original) The angular measuring device in accordance with claim 2, wherein said coupler comprises:

two diametrically oppositely located tongues that are fastened to said stator; and
two further diametrically oppositely located tongues, which are offset by 90° with respect to said two diametrically oppositely located tongues that are fastened to said stator, and wherein clamping takes place between said two further diametrically oppositely located tongues and said stationary object.

12. (original) The angular measuring device in accordance with claim 3, wherein said coupler comprises:

two diametrically oppositely located tongues that are fastened to said stator; and
two further diametrically oppositely located tongues, which are offset by 90° with respect to said two diametrically oppositely located tongues that are fastened to said stator, and wherein clamping takes place between said two further diametrically oppositely located tongues and said stationary object.

13. (original) The angular measuring device in accordance with claim 4, wherein said coupler comprises:

two diametrically oppositely located tongues that are fastened to said stator; and
two further diametrically oppositely located tongues, which are offset by 90° with
respect to said two diametrically oppositely located tongues that are fastened to said
stator, and wherein clamping takes place between said two further diametrically
oppositely located tongues and said stationary object.

14. (original) The angular measuring device in accordance with claim 10,
wherein one of said two further diametrically oppositely located tongues comprises a
section that is fastened on a ring.

15. (original) The angular measuring device in accordance with claim 14,
wherein said contact face is fastened on said ring.

16. (previously amended) An angle measuring device for measuring an
angular position of a stationary object with respect to an object which is rotatable around
an axis of rotation, comprising:

a rotor comprising a graduation, which is connected to said rotatable
object, which rotates about an axis of rotation;

a stator comprising a scanning unit for scanning said graduation, which

moves in relation to said scanning unit;

a coupler fastened to said stator so as to seat said stator on said stationary object that comprises a contact face which extends transversely with respect to said axis of rotation, wherein said coupler comprises a contact face that extends transversely with respect to said axis of rotation and engages said contact face of said stationary object so that a clamping force is generated so as to fasten said coupler to said stationary object and wherein said coupler is fixed against relative rotation, but is radially and/or axially elastic; and

wherein said rotor is connected with said rotating object by an axially extending screw, and said clamping force takes place by axial displacement of said screw.

17. (currently amended) An angle measuring device for measuring an angular position of a stationary object with respect to an object which is rotatable around an axis of rotation, comprising:

a rotor comprising a graduation, said rotor is connected to said rotatable object which rotates about an axis of rotation;

a stator comprising a scanning unit for scanning said graduation, which rotates in relation to said scanning unit;

a coupler fastened to said stationary object so as to seat said stator on said coupler that comprises a contact face which extends transversely with respect to said axis of rotation, wherein said stator comprises a contact face that extends transversely with respect to said axis of rotation and clampingly engages said contact face of said coupler so that a clamping force is generated so as to fasten said stator to said coupler and wherein said coupler is fixed against relative rotation, but is radially and/or axially elastic.

18. (previously amended) An angle measuring device for measuring an angular position of a stationary object with respect to an object which is rotatable around an axis of rotation, comprising:

a rotor comprising a graduation, said rotor is connected to said rotatable object which rotates about an axis of rotation;

a stator comprising a scanning unit for scanning said graduation, which moves in relation to said scanning unit;

a coupler fastened to said stationary object so as to seat said stator on said coupler that comprises a contact face which extends transversely with respect to said axis of rotation, wherein said stator comprises a contact face that extends transversely with respect to said axis of rotation and engages said contact face of said coupler so that a

clamping force is generated so as to fasten said stator to said coupler and wherein said coupler is fixed against relative rotation, but is radially and/or axially elastic; and

wherein said rotor is connected with said rotating object by an axially extending screw, and said clamping force takes place by axial displacement of said screw.

19. (original) A method for mounting a stator of an angle measuring device, comprising a rotor rotating around an axis of rotation, on a stationary object, said method comprising:

attaching a radially and/or axially compensating coupler to said stator of said angle measuring device;

axially moving said angle measuring device toward said stationary object, wherein a contact face, which extends transversely with respect to said axis of rotation about which a rotor rotates, of said coupler comes into contact with a contact face, which extends transversely with respect to said axis of rotation, of said stationary object;

supporting said contact face of said coupler on said contact face of said stationary object, wherein during said axially moving said angle measuring device toward said stationary object said contact face of said coupler is radially displaced until said contact face of said coupler is pushed against a further face of said stationary object and clamps said coupler in a manner fixed against relative rotation.

20. (currently amended) A method for mounting a stator of an angle measuring device, comprising a rotor rotating around an axis of rotation, on a stationary object, said method comprising:

attaching a radially and/or axially compensating coupler to said stator of said angle measuring device;

axially moving said angle measuring device toward said stationary object, wherein a contact face of said coupler comes into contact with a contact face of said stationary object so that a clamping engagement between said contact face of said coupler and said contact face of said stationary object results;

supporting said contact face of said coupler on said contact face of said stationary object, wherein by said axially moving said angle measuring device toward said stationary object said coupler is clamped to said stationary object in a manner fixed against relative rotation.

21. (previously added) The angle measuring device of claim 1, wherein said clamping force is generated by axial displacement of said stator.

22. (previously added) The angle measuring device of claim 17, wherein said clamping force is generated by axial displacement of said stator.